

## OFP Series LED Display Specifications

### Introduction

OFP Series:16:9 Golden Ratio LED Display with 600×337.5mm size, this product will be targeting small pixel pitch LED display market. A variety of outdoor pixel pitch can be met. For module, power supply and receiver card, easy to install and disassemble. The cabinet has good heat dissipation, no noise, energy saving and environmental protection. Excellent design, top quality, perfect visual performance, better color consistency. Outdoor installation, no need to reserve the maintenance channel. Widely used in commercial display, outdoor fixed advertising, auditorium,conference room,banquet etc.



### Specifications

Product model	OFP-A1	OFP-A2	OFP-A3
Pixel Pitch(mm)	1.875	2.5	3.125
Module Size(mm)	150 x 337.5	300 x 337.5	300 x 337.5
Module Resolution(dot)	80 x 180	120 x 135	96 x 108
Module Assembly	4 x 1	2 x 1	2 x 1
Panel Size(w x h x d)(mm)	600 x 337.5 x 50	600 x 337.5 x 50	600 x 337.5 x 50
Panel Resolution(dot)	320 x 180	240 x 135	192 x 108
LED Type	SMD1415	SMD1415	SMD1415
Brightness(cd/m <sup>2</sup> )	4500	4500	5000
Support Input	Composite,S-Vido,Component,VGA,DVI,HDMI,HD_SDI		
Horizontal Viewing Angle	140°		
Vertical Viewing Angle	140°		
Gray Level	16384		
Refresh Rate(Hz)	3840Hz		
Max. AC power consumption	700W/m <sup>2</sup>		
Avg. AC power consumption	350W/m <sup>2</sup>		
Voltage	AC100~240 50/60HZ		
Operate Temp(°C)	-30°C~+50°C		
Storage Temp(°C)	-40 ~ 80 °C		
Operating Humidity	10~95% RH		
Protection grade	IP65		
Operating Environment	Outdoor		
Cabinet Material	Aluminum alloy		
LED Lifetime(H)	100,000		
Weight(kg/pc)	6		

\*Notes: Specifications are slightly different according to different configurations.

Images

