



### Features

- LED backlight technology with ultra HD 3840 × 2160
- High fidelity digital processing, brilliant and vivid video
- Wide view of field: 178° (H)/ 178° (V)
- User-friendly operation menu, which is simple to operate
- Lower power consumption and long life cycle
- VESA stand bracket
- Conformal coating on the major circuit board (power board) significantly reduces these risks from such environments by protecting LCD display from salt, dust, iron powder, humidity, etc
- Support abundant interfaces
- The screen features a symmetrical four-edge bezel design, combining sleek aesthetics with practical functionality.
- Operational Hours. 24/7 Operation

No.	Name	Item	Parameter	
1	LCD Panel	BOE	Size	86"
			Brightness	500 nit
			Max. resolution	3840*2160
			Viewing Angle	178°(H), 178°(V)
			Display Area	W1895.04*H1065.96mm
			Contrast Ratio	3000:1
			Refresh Rate	60Hz
			Ratio	16:9
			Lifetime	60,000 hours
2	Main Board	Interface	HDMI 2.0*3, USB 2.0*1, USB 3.0*1, RS232C*1,RJ45*1,WIFI, Headphone output, VGA, Audio, AV,Y PB PR, TF card input	
		Operating System	Android 14.0	
3	Others	Power supply	AC100V~240V, 50/60Hz	
		Operating temperature	0°C~60°C	
		Storage temperature	-20°C~60°C	
		Power consumption	Max 350W, Avg 1W	
		Installation	Wall-mounted	
4	Cabinet	Dimension	1951.4(W)×1125(H)×99.7(D)mm	
		Weight	80kg	

*Note: All product specifications are for reference only and subject to change without prior notice.*

